



Wall Products International, INC.

201 NE 21st St, Fort Worth, Tx 76164

phone: 800.446.7124 or 817.626.1987

fax: 817.626.0821

www.murcowall.com email: murco@murcowall.com

---

## SPECIFICATION AND DATA SHEET

### PRODUCT NAME:

Quick Hide Interior Semi-Gloss Paint

### MANUFACTURER:

Murphy Wall Products International, Inc.  
201 NE 21st St, Fort Worth, Tx, 76164  
800.446.7124

### ADVANTAGES:

- Economical
- Washable
- Good Coverage
- Low Odor
- Clean up with water

### PRODUCT DESCRIPTION:

An economical, heavy bodied paint, durable combination paint and primer that has good coverage and can hide most colors in one coat. It dries to a bright white color, has low odor. This paint can eliminate the use of an undercoat or primer. Interior use only.

### RECOMMENDED USES:

Quick Hide Semi-Gloss provides an exceptional finish to ceilings and walls. It can be used as a primer/sealer and it is self priming over properly prepared surfaces. Interior Use only.

### SURFACES PREPARATION:

General: All surfaces must be clear of dust, oil, grease, dirt, loose paint and rust. Mildew should be removed with a germicide. Concrete and masonry should be free from marks and dust, and cured for 30 days. Product can be applied to shiny surfaces, but for best performance de-gloss with sand paper if possible.

\*The Society for Protective Coatings (SSPC) surface preparation standards should be followed for best performance.

### METHOD OF APPLICATION:

Stir thoroughly before and during use. Apply only when surface and air temperatures are between 50° degrees and 90° F.

Maintain a wet edge to avoid lap marks.

Thinning is not recommended, but if necessary, no more than four ounces per gallon of clean water.

Two coats are recommended for best performance.

**BRUSH:** High quality polyester brush.

**ROLL:** 3/8-1/2" nap high quality synthetic roller cover.

**AIRLESS:** Equipment must be clean prior to start. Test your spray pattern and flow before use.

**CLEAN UP:** Clean tools and equipment with warm, soapy water.



## Technical Data

<b>Resin Type</b>	Proprietary latex
<b>Finish</b>	Semi-Gloss, 40 - 50 GU @ 60°
<b>Colors</b>	White
<b>Viscosity</b>	95 - 105 KU
<b>Solids by Weight</b>	41% ± 3%
<b>Solids by Volume</b>	32% ± 2%
<b>Flashpoint</b>	Above 200° F
<b>Density</b>	10.3 - 10.5 lbs./Gallon
<b>Volatile Organic Compounds (VOC)</b>	Less than 10 grams per Liter
<b>Coverage</b>	300 - 350 ft <sup>2</sup> /Gallon
<b>Container Size</b>	1 & 5 Gallon pails. Larger sizes upon request
<b>Dry Time</b>	Dust Free: 1/2 hour Tack Free: 1 hour Recoat: 2 hours; overnight is recommended

**CAUTION: KEEP OUR OF REACH OF CHILDREN**

**DO NOT TAKE INTERNALLY**

**DO NOT FREEZE**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NOISH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1. 800. 424. LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead)

MADE IN THE U.S.A