



Wall Products International, INC.

201 NE 21st St, Fort Worth, Tx 76164

phone: 800.446.7124 or 817.626.1987

fax: 817.626.0821

www.murcowall.com email: murco@murcowall.com

SPECIFICATION AND DATA SHEET

PRODUCT NAME:

Quick Hide Interior Flat Paint

MANUFACTURER:

Murphy Wall Products International, Inc.
201 NE 21st St, Fort Worth, Tx, 76164
800.446.7124

ADVANTAGES:

- Economical
- Bright White
- Good Coverage
- Low Odor
- Clean up with water

PRODUCT DESCRIPTION:

An economical, heavy bodied paint that has good coverage and can hide most colors in one coat. It dries to a bright white color, has low odor and can be used as an undercoat.

RECOMMENDED USES:

Quick Hide Flat provides an exceptional finish to ceilings and walls, it also makes a great undercoat when texturing. Interior Use only.

SURFACES PREPARATION:

General: All surfaces must be clear of dust, oil, grease, dirt, loose paint and rust. Mildew should be removed with a germicide. Concrete and masonry should be free from marks and dust, and cured for 30 days. Product can be applied to shiny surfaces, but for best performance de-gloss with sand paper if possible.

*The Society for Protective Coatings (SSPC) surface preparation standards should be followed for best performance.

METHOD OF APPLICATION:

Stir thoroughly before and during use. Apply only when surface and air temperatures are between 50° degrees and 90° F.

Maintain a wet edge to avoid lap marks.

Thinning is not recommended, but if necessary, no more than four ounces per gallon of clean water.

Two coats are recommended for best performance.

BRUSH: High quality polyester brush.

ROLL: 3/8-1/2" nap high quality synthetic roller cover.

AIRLESS: Equipment must be clean prior to start. Test your spray pattern and flow before use.

CLEAN UP: Clean tools and equipment with warm, soapy water.



Technical Data

Resin Type	Proprietary latex
Finish	Flat, <5 GU @ 60°
Colors	White
Viscosity	95 - 105 KU
Solids by Weight	40% ± 3%
Solids by Volume	32% ± 2%
Flashpoint	Above 200° F
Density	10.5 - 10.8 lbs./Gallon
Volatile Organic Compounds (VOC)	Less than 5 grams per Liter
Coverage	300 - 350 ft ² /Gallon
Container Size	1 & 5 Gallon pails. Larger sizes upon request
Dry Time	Dust Free: 1/2 hour Tack Free: 1 hour Recoat: 2 hours; overnight is recommended

CAUTION: KEEP OUR OF REACH OF CHILDREN

DO NOT TAKE INTERNALLY

DO NOT FREEZE

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NOISH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1. 800. 424. LEAD or log on to www.epa.gov/lead

MADE IN THE U.S.A